

539,688

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



Rec'd PCT/PTO 16 JUN 2005



10/539688

(43) International Publication Date
28 April 2005 (28.04.2005)


PCT

(10) International Publication Number
WO 2005/038177 A1

- (51) International Patent Classification⁷: E05B 65/46, E05C 19/02, A47B 88/04
- (21) International Application Number: PCT/EP2004/052535
- (22) International Filing Date: 14 October 2004 (14.10.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: RM2003U000171 15 October 2003 (15.10.2003) IT
- (71) Applicant (for all designated States except US): ARTURO SALICE S.P.A. [IT/IT]; Via Provinciale Novedrate 10, I-22060 Novedrate (IT).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): SALICE, Luciano [IT/IT]; Via Ronco, 30, I-22060 Carimate (IT).
- (74) Agent: GERVASI, Gemma; Notarbartolo & Gervasi S.p.A., Corso di Porta Vittoria 9, I-20122 Milan (IT).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Declaration under Rule 4.17:
— of inventorship (Rule 4.17(iv)) for US only
- Published:
— with international search report

[Continued on next page]

(54) Title: OPENING AND CLOSING LATCH DEVICE FOR FURNITURE



(57) Abstract: Latch device composed of a container (51) in which there is a slider (52), inserted in a guide (60), controlled in translation by a spring (53) and comprising a hook (68) to catch a hooking element (59) placed on a door. A track (40), with the bottom defining the profile of a cam on one side of the guide (60), is travelled along by a ball (73) placed on the slider (52) and held pressed by a spring (72) against the bottom of the track (40) to determine the four open, closed, released and locked positions of the door according to the position of the ball in the track.

WO 2005/038177 A1



— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

OPENING AND CLOSING LATCH DEVICE FOR FURNITURE

Field of the invention

The present invention relates to an opening and closing device for furniture provided with a latch adapted to facilitate operations to open and close movable parts of furniture, for brevity also called latch.

State of the art

Known latches have the function of facilitating opening or closing of the doors of furniture or drawers, according to the application for which they have been designed. These latches produce a slight contrasting force during the closing action that is accumulated by elastic elements capable of releasing it in a subsequent phase when the reverse operation of opening is implemented.

If a latch is used to facilitate opening of a drawer or door, the latter is maintained in its closed position by suitable and known devices, which can either be separate from the latch or integral with it, for example hooks, magnets or the like.

To open the drawer or door it is first necessary to apply a slight thrust to the drawer or door to release the latch, which returns the elastic energy accumulated during the closing operation and exerts a force on the drawer, generally created by springs, in the opening direction. An advantage of these devices is that they also make it possible not to use handles or other similar grasping elements on the drawer, which are not always appreciated for aesthetic or other reasons.

Generally, one part of the elements constituting the latches is placed on fixed elements of the furniture to which the drawer belongs and another part on the drawer itself; moreover, these are constituted by a large number of elements that can make assembly by inexperienced personnel difficult.

Some known latches are described in the documents DE 29507917U, DE 3816091, DE 19753319 and DE 10008350. However, these are devices that are complex to manufacture or to mount, some of which are too delicate to guarantee long-lasting operation.

Summary of the invention

A main purpose of the present invention is therefore to produce a latch that overcomes the drawbacks indicated hereinbefore in a simple and inexpensive way and which is compact, sturdy and easy to apply to furniture, particularly to doors.

Therefore, the present invention solves the problems mentioned hereinbefore by producing a latch with the characteristics claimed in claim 1.

In particular, the invention relates to a latch device, which can be locked and released by the action of an external force produced by one or more springs, comprising a slider. The slider is suitable to translate along a guide, integral with a fixed part of the furniture, inclined by an angle differing from zero with respect to the direction in which the external closing force is applied, and has a hook that may be caught by the movable part of the furniture. Moreover, elements suitable to lock or to release the slider according to the function implemented are provided between the slider and the container.

Thanks to the solution of the invention, the latch has a simple and compact structure that can be applied simply to drawers or doors of furniture, thus guaranteeing exact positioning with respect to the parts and consequently its correct operation. It is also characterized by fast and easy mounting that can be performed without the use of special tools.

The latch device is also sturdy and secure against any danger of becoming detached from the furniture element to which it is fixed. The latch also has compression springs or equivalent elastic means capable of controlling sufficient opening travel to allow easy manual grip to complete opening of the drawer or, if necessary, even to completely eliminate this action.

The dependent claims describe preferred embodiments of the invention.

Brief description of the Figures.

Further characteristics and advantages of the invention shall become more evident in the light of the detailed description of preferred, although not exclusive, embodiments of a latch, provided as non-limiting examples, with the aid of the accompanying drawings, wherein:

Figure 1 shows a side view of the latch device of the invention in a first operating position;

Figure 2 shows a side view of the latch device in Figure 1 in a second operating position;

Figure 3 shows an exploded axonometric view of the latch device in Figure 1;

Figure 4 shows an axonometric view of an element forming the latch device in Figure 1;

Figure 5 shows an axonometric view of an element forming the latch device in Figure 1;

Figure 6 shows a side section of an embodiment of the latch device of the invention;

5 Figure 7 shows an exploded axonometric view of the latch device in Figure 6;

Figure 8 shows four different operating phases of the latch according to the invention.

Detailed description of preferred embodiments

10 With reference to the Figures cited, a latch device is represented, globally referenced with the reference T, generally, although not necessarily, fixed in one part thereof to a suitable structure of furniture 57, and in another part thereof to a door 58. It is however possible to kinetically invert the furniture parts on which the two parts forming the latch are fixed, however without departing from the sphere of the invention.

15 The part of the latch T destined to be fixed to the furniture 57 with suitable means that are not described in detail, comprises a box or container 51 with a first groove or longitudinal cavity defining a sliding guide 60. In the guide 60 there are the slider 52, the helical spring 53 or another similar spring, which rests with one end on a shoulder or end of the guide and with the other end on the slider 52, on
20 which a shank 65 is provided to improve contact with the spring 53. The container 51 has a cover 54 to close the open side of the guide 60.

In an advantageous embodiment part of the container is provided with an insert 50 essentially triangular in shape, which forms one side of the guide 60, or part of one side, to facilitate manufacture and assembly. However, the insert 50 may
25 alternatively also be eliminated to produce the container 51 in one piece.

The guide 60 is inclined, with respect to the direction of application of the force F acting on the slider 52, of an angle α , predetermined and defined according to the door or furniture part to be opened.

There is provided, on the side of the guide 60, a second groove defining a track
30 40 with different depths according to areas defining a path with a cam profile.

The slider 52 also has a seat 71 with a rectangular plane, closed on the bottom, in which is placed a flat spring 72 bent in the shape of a V, on the outward facing side of which a ball 73 rests. The flat spring 72 thus pushes the ball 73 towards

the bottom of the track 40 to make it travel along the path. A third groove 67 facilitates attachment of the spring 72 in its seat 71.

The track 40 is constituted by a longer longitudinal section 27, the bottom of which varies in thickness and forms an inclined ramp terminating with a step 28, which marks the limit separating it from a transverse section 29 slightly curved in the plane. The bottom of the transverse section 29 has two sections with levels 29', 29'' slightly staggered, in the deepest of which 29'' a seat 30 is provided in the shape of a spherical cap. Running parallel to the section 27 is a second shorter longitudinal section 31, which joins with the front part of the section 27 by means of a section 32, the bottom of which is inclined, and at the end of which a short inclined ramp 33 is positioned to form a further step 34 in the connection point with the section 27.

Fig. 8 shows four positions of the latch, which show its operation between an open position and a locked position and again in an open position. The positions are indicated with the letters a), b), c), d) and also define four corresponding positions of the ball 73 along the track of the cover. Here the positions are shown as transparency views through the surface of the insert 50. In position a) the hook 68 is in the outermost position, and therefore the hooking element 59 and the door connected to it can move freely. When the door 58 is pushed towards the closing position, the hooking element 59 knocks against the hook 68 with a force F , the component thereof parallel to the axis of the guide 60 pushes the slider 52 inside the guide 60 compressing the spring 53 to reach the position shown in Figure 2.

During this sliding, the hook 68 engages the hooking edge 62 of the hooking element 59, catching it. At this point as the ball 73 cannot travel along the section 32 as it is obstructed by the step 34, it travels along the ramp 27 and passes beyond the step 28. Here inclination of the shank of the V-shaped spring 72 pushes the ball 73 along the deepest part 29'' of the section 29 until it enters the seat 30 in the form of spherical cap, becoming locked in the position c). In this position the slider 52 cannot slide in the groove and the hook 68 locks the hooking element 59, so that the furniture part remains locked in its closed position even if no external force is applied thereto.

The operation to open the door or drawer is instead carried out in the following way. After a successive slight thrust in the closing direction of the door, the ball 73 is moved from the seat 30 towards the shallowest part 29' of the section 29 and the spring 72 pushes it into the position d). By removing the external force on the furniture part, the helical spring 53 pushes the slider 52 towards the outside and the ball 73 travels along the sections 31 and 32 passing beyond the ramp 33 and the step 34, returning to the initial condition a) wherein the furniture part is released.

Advantageously, the hooking element can be constituted by a cavity 61 partly open towards the opposed flat surfaces so as to easily produce the hooking edge 62, even with a moulding process. The bottom 63 constitutes the thrust element of the hook 68 when the latch is in operation, making it slide in combination with the oblique movement in the inclined direction of the angle α , until it is positioned behind the hooking edge 62, as shown in Figures 2 and 6.

The cover 54 is also provided with shanks 76 suitable to be housed in corresponding holes 75 of the container 51 to allow integral assembly of the two parts.

An embodiment of the latch conforming to the invention is shown in Figures 6 and 7. The container 81 has an essentially hollow trapezoidal shape inside which a sliding guide 90 is placed. One of the sides of the container is open and, in the mounted position of the latch, this side is closed by a triangular insert 80, one of the sides thereof defining a side of the guide 90. The triangular insert 80 also has the function of resting on the furniture, with a suitable reference stop 84. Advantageously, although not necessarily, the track 40 can be provided on one side of the triangular insert 80. This element is suitably fixed to the container 81 by means of fixing means of known type, not shown.

From the description above it is apparent that the latch device of the invention is composed of a minimum number of components, is simple to assemble and can be mounted on furniture with an operation that is not difficult even for inexperienced personnel.

The particular embodiments described herein do not limit the content of this application, which covers all the embodiments of the invention defined by the claims.

CLAIMS

1. Opening and closing latch device (T), adapted to facilitate closing and/or opening of a movable part (58) of furniture with respect to the furniture (57), comprising a container (51, 81) defining an internal cavity with at least one open
5 side and comprising a sliding guide (60, 90),

characterised in that it also comprises:

- a sliding element (52), placed in the sliding guide and comprising a hook (68) at a first end, suitable to catch a hooking element (59) integral with said movable part (58),

10 - elastic means (53), placed between the sliding element (52) and the container (51), so that the elastic means (53) exert an elastic force on the sliding element (52) suitable to make it slide, reacting on said container (51),

- a track (40), placed on one side of the sliding guide (60, 90), with surface of the bottom defining a cam path and the plan layout of which forms a closed
15 geometrical figure,

- tappet means (73), integral with the sliding element (52), suitable to travel along the cam path, so as to define a number of positions of the sliding element (52), corresponding to a release position, a lock position and two intermediate opening and closing positions of said movable part (58),

20 and in that the sliding guide (60, 90) is inclined of an angle (α) with respect to the direction along which a closing and opening movement takes place between the movable part (58) and the furniture (57).

2. Latch device according the claim 1, wherein the container (51, 81) comprises an insert (50) essentially triangular in shape, one side of which defines a side of
25 the sliding guide (60, 90).

3. Latch device according the claim 2, wherein the track (40) is provided on the side of the sliding guide (60, 90) constituted by said insert (50, 80).

4. Latch device according the claim 3, wherein the container (51) comprises a cover (54), forming one of the sides of the cavity, and a base with connection
30 means (76) suitable to join the cover to the base.

5. Latch device according the claim 4, wherein the tappet means are formed of a ball (73) held in pressure against the bottom of the track (40) by a spring (72).




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP2004/052535

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 E05B65/46 E05C19/02 A47B88/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 E05C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 401 067 A (KUROSAKI MUTSUO ET AL) 28 March 1995 (1995-03-28) column 12, line 38 - column 15, line 8; figures 11-18	1-5
A	US 4 792 165 A (NISHIMURA TAMOTSU) 20 December 1988 (1988-12-20) column 4, line 27 - column 6, line 6; figures 1-12	1-5
A	EP 0 766 939 A (PIOLE SA) 9 April 1997 (1997-04-09) column 3, line 2 - column 3, line 44; figures 1-4	1-3
A	US 5 072 974 A (HENNE ET AL) 17 December 1991 (1991-12-17) figures 1-11	1
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

G document member of the same patent family

Date of the actual completion of the international search

3 March 2005

Date of mailing of the international search report

10/03/2005

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Friedrich, A

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP2004/052535

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 197 53 319 A1 (SARNATECH PAULMANN & CRONE GMBH, 58511 LUEDENSCHIED, DE; SARNATECH PAU) 23 July 1998 (1998-07-23) cited in the application the whole document -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP2004/052535

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5401067	A	28-03-1995	JP 3276672 B2	22-04-2002
			JP 5340152 A	21-12-1993
			JP 3200165 B2	20-08-2001
			JP 5340153 A	21-12-1993
US 4792165	A	20-12-1988	NONE	
EP 0766939	A	09-04-1997	FR 2739268 A1	04-04-1997
			DE 69627443 D1	22-05-2003
			DE 69627443 T2	24-12-2003
			EP 0766939 A2	09-04-1997
			ES 2197940 T3	16-01-2004
US 5072974	A	17-12-1991	NONE	
DE 19753319	A1	23-07-1998	NONE	